elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**



# EC690974F

## PANEL-MOUNT VERT. INTERLOCKED SOCKET WITH FUSE HOLDER IP65 380V 3P+E 32A

Industrial > Plugs and sockets > Switched interlocked > Vertical - with fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - flush-mount

### Technical Symbols/Marks/Approvals

IP65 | IK08 | HF | CE | RoHS II | MADE IN ITALY

### Norms

EN 60309-1 EN 60309-2 EN 60309-4

## Description

Flush-mounted fixed interlocked socket with fuse base. IP65 protection rating. LED indicator for blown fuse. gG type fuses 10.3x38 mm (not included). Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 20° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs.
3P+E 32A 380-415V~ 6h

## Etim

### GROUP EG000014 - Industrial sockets/plug applications

### CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

| | | | | | |
|---|---|---|---|---|---|
| **Number of poles** | 4 | **Degree of protection (IP)** | IP65 | **Model** | Top cover |
| **Housing material** | Plastic | **IEC-amperage** | 32 A | **Voltage according to EN 60309-2** | 400 V (50+60 Hz) red |
| **Clock hour position** | 6 h | **Identification colour** | Red | **Contact material** | CuZn |
| **Surface coating contacts** | Untreated | **Military model** | No | **Protection** | Cylindrical fuse |
| **Switch** | Mechanical locking | **With earth leakage switch** | No | **Empty locations on mounting rail** | No |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Documentation available for download



Certification

IMQ_CA02.05814_2025_32A_IVCBF.pdf

## Barcode

8033954872111

**Unit**

1 NR

0.125x0.315x0.155 [m]

1.073 [kg]

8059307217064

**Cardboard**

10 NR

0.4x0.605x0.35 [m]

10.73 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.