

**EC690981F**

**WALL-MOUNT HORIZ. INTERLOCKED SOCKET WITH FUSE HOLDER IP44 380V3P+N+E 32A**



Industrial > Plugs and sockets > Switched interlocked > Horizontal - with fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip44 - wall-mount

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2 EN 60309-4

**Description**

Interlocked switched surface-mounting socket with fuse base. Protection rating IP44. LED blown fuse indicator. gG type fuses 10.3x38 mm (not included). Dimensions: 196x146x77 mm. 20° inclined socket. Switch type AC23A - 10 kA. Ergonomic handle padlockable in ON/OFF position. Stainless steel cover springs. 3P+N+E 32A 346-415V~ 6h

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)**

|                                 |                    |                                  |      |   |                      |
|---------------------------------|--------------------|----------------------------------|------|---|----------------------|
| <b>Number of poles</b>          | 5                  | <b>Degree of protection (IP)</b> | IP44 | <b>Model</b>                            | Base unit and cover  |
| <b>Housing material</b>         | Plastic            | <b>IEC-amperage</b>              | 32 A | <b>Voltage according to EN 60309-2</b>  | 400 V (50+60 Hz) red |
| <b>Clock hour position</b>      | 6 h                | <b>Identification colour</b>     | Red  | <b>Contact material</b>                 | CuZn                 |
| <b>Surface coating contacts</b> | Untreated          | <b>Military model</b>            | No   | <b>Protection</b>                       | Cylindrical fuse     |
| <b>Switch</b>                   | Mechanical locking | <b>With earth leakage switch</b> | No   | <b>Empty locations on mounting rail</b> | No                   |

**Documentation available for download**



**Certification**

IMQ\_CA02.05695\_2025\_32A\_IOC.BF.pdf

## Barcode



8033954871855

**Unit**

1 NR

0.2x0.154x0.145 [m]

0.858 [kg]



8059307217101

**Cardboard**

10 NR

0.605x0.4x0.35 [m]

8.58 [kg]