

**EC690994**



**PANEL-MOUNT VERT. INTERLOCKED SOCKET IP65  
380V 3P+N+E 32A**

Industrial > Plugs and sockets > Switched interlocked > Vertical - without fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - flush-mount

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2 EN 60309-4

**Description**

Flush-mounted fixed interlocked socket. IP65 protection rating. Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 20° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 3P+N+E 32A 346-415V~ 6h

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)**

<b>Number of poles</b>	5	<b>Degree of protection (IP)</b>	IP65	<b>Model</b>	Top cover
<b>Housing material</b>	Plastic	<b>IEC-ampereage</b>	32 A	<b>Voltage according to EN 60309-2</b>	400 V (50+60 Hz) red
<b>Clock hour position</b>	6 h	<b>Identification colour</b>	Red	<b>Contact material</b>	CuZn
<b>Surface coating contacts</b>	Untreated	<b>Military model</b>	No	<b>Protection</b>	None
<b>Switch</b>	Mechanical locking	<b>With earth leakage switch</b>	No	<b>Empty locations on mounting rail</b>	No

**Documentation available for download**



**Certification**

IMQ\_CA02.05815\_2025\_32A\_IVSBF.pdf

## Barcode



8053676576012

**Unit**

1 NR

0.295x0.12x0.15 [m]

0.76 [kg]



8059307217194

**Cardboard**

10 NR

0.605x0.4x0.35 [m]

7.6 [kg]