

EC690994F



PANEL-MOUNT VERT. INTERLOCKED SOCKET WITH FUSE HOLDER IP65 380V3P+N+E 32A

Industrial > Plugs and sockets > Switched interlocked > Vertical - with fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - flush-mount

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Flush-mounted fixed interlocked socket with fuse base. IP65 protection rating. LED indicator for blown fuse. gG type fuses 10.3x38 mm (not included). Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 20° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 3P+N+E 32A 346-415V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications
CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	5	Degree of protection (IP)	IP65	Model	Top cover
Housing material	Plastic	IEC-amperage	32 A	Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h	Identification colour	Red	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	Cylindrical fuse
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Documentation available for download

Certification

IMQ_CA02.05814_2025_32A_IVCBF.pdf

Barcode



8033954872128

Unit

1 NR

0.125x0.315x0.155 [m]

1.073 [kg]



8059307217224

Cardboard

10 NR

0.4x0.605x0.35 [m]

10.73 [kg]