

EC69102

PANEL-MOUNT INCLINED SOCKET IP44 110/130V 2P+E 32A



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip44 - 32 a

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2

Description

Industrial flush-mounted socket, type EN 60309. IP44 protection rating. 20° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).
2P+E 32A 100-130V~ 4h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)

| | | | | | |
|-------------------------------------|-----------|----------------------------------|-----------|--|----------------------------|
| Number of poles | 3 | Degree of protection (IP) | IP44 | Material | Plastic |
| RAL-number | 1023 | IEC-ampere | 32 A | Voltage according to EN 60309-2 | 110 V (50+60 Hz) yellow |
| Clock hour position | 4 h | Identification colour | Yellow | Connection system | Screwed terminal |
| Insert direction | Straight | Surface coating contacts | Untreated | Military model | No |
| Rated voltage | 100-130 V | Rated frequency | 50-60 Hz | Flange size vertical | 97 mm |
| Drill hole distance vertical | 73 mm | Flange size horizontal | 80 mm | Drill hole distance horizontal | 60 mm |

Documentation available for download



Barcode



8033576770772

Unit

1 NR

0.1947 [kg]



8057711591183

Pack

10 NR

1.947 [kg]



8033576771540

Cardboard

60 NR

11.682 [kg]