

**EC69252**



**PANEL-MOUNT INCLINED SOCKET  
IP44 220/240V 2P+E 32A**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip44 - 32 a

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2

**Description**

Industrial flush-mount socket, type EN 60309. IP44 protection rating. 20° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included).  
2P+E 32A 200-250V~ 6h

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**  
**CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)**

<b>Number of poles</b>	3	<b>Degree of protection (IP)</b>	IP44	<b>Material</b>	Plastic
<b>RAL-number</b>	5017	<b>IEC-amperage</b>	32 A	<b>Voltage according to EN 60309-2</b>	230 V (50+60 Hz) blue
<b>Clock hour position</b>	6 h	<b>Identification colour</b>	Blue	<b>Connection system</b>	Screwed terminal
<b>Insert direction</b>	Straight	<b>Surface coating contacts</b>	Untreated	<b>Military model</b>	No
<b>Rated voltage</b>	200-250 A	<b>Rated frequency</b>	50-60 Hz	<b>Flange size vertical</b>	97 mm
<b>Drill hole distance vertical</b>	73 mm	<b>Flange size horizontal</b>	80 mm	<b>Drill hole distance horizontal</b>	60 mm

**Documentation available for download**

**Certification**

IMQ\_CA02.05864\_2025\_32A.pdf

## Barcode



8033576770796

**Unit**

1 NR

0.1972 [kg]



8057711591220

**Pack**

10 NR

1.972 [kg]



8033576771526

**Cardboard**

60 NR

11.832 [kg]