

EC69253



**PANEL-MOUNT INCLINED SOCKET
IP44 220/240V 3P+E 32A**

Industrial > Plugs and sockets > Panel and wall-mount > Panel sockets > Panel-mounted cee socket outlet (iec 60309) > Ip44 - 32 a



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2

Description

Industrial flush-mount socket, type EN 60309. IP44 protection rating. 20° tilt. Pre-screwed screw terminals oriented in the same direction for quick wiring. Stainless steel cover springs. Panel gasket included. Recommended mounting with 3.5x16 or M4x20 self-tapping screws (not included). 3P+E 32A 200-250V~ 9h

Etim

GROUP EG000014 - Industrial sockets/plug applications
CLASS EC001317 - Panel-mounted CEE socket outlet (IEC 60309)

| | | | | | |
|-------------------------------------|-----------|----------------------------------|-----------|--|-----------------------|
| Number of poles | 4 | Degree of protection (IP) | IP44 | Material | Plastic |
| RAL-number | 5017 | IEC-amperage | 32 A | Voltage according to EN 60309-2 | 230 V (50+60 Hz) blue |
| Clock hour position | 9 h | Identification colour | Blue | Connection system | Screwed terminal |
| Insert direction | Straight | Surface coating contacts | Untreated | Military model | No |
| Rated voltage | 200-250 V | Rated frequency | 50-60 Hz | Flange size vertical | 97 mm |
| Drill hole distance vertical | 73 mm | Flange size horizontal | 80 mm | Drill hole distance horizontal | 60 mm |

Documentation available for download

Certification

IMQ_CA02.05864_2025_32A.pdf

Barcode



8033576770802

Unit

1 NR

0.1972 [kg]



8057711591237

Pack

10 NR

0.19x0.29x0.165 [m]

1.972 [kg]



8033576771519

Cardboard

60 NR

11.832 [kg]