

EC6925841F



**WALL-MOUNT VERT. INTERLOCKED
SOCKET WITH FUSE HOLDER IP65
220V 2P+E 63A**



IMMAGINE
RAPPRESENTATIVA

REPRESENTATIVE
IMAGE

Industrial > Plugs and sockets > Switched interlocked > Vertical
- with fuse holder > Cee socket outlet, disconnectable (iec
60309) > Ip65 - wall-mount

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Wall-mounted fixed interlocked socket with fuse base. IP65 protection rating. gG type fuses 15x36 mm (not included). Dimensions: 118x277x85 mm. Fixing centers: 141+118x100 mm. 15° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 2P+E 63A 200-250V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	3	Degree of protection (IP)	IP65	Model	Base unit and cover
Housing material	Plastic	IEC-ampereage	63 A	Voltage according to EN 60309-2	230 V (50+60 Hz) blue
Clock hour position	6 h	Identification colour	Blue	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	D0-system
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Barcode



8033954876379

Unit

1 NR

0.295x0.12x0.15 [m]

1.7336 [kg]



8059307217989

Cardboard

10 NR

0.605x0.4x0.35 [m]

17.336 [kg]