

EC692584F



**PANEL-MOUNT VERT. INTERLOCKED
SOCKET WITH FUSE HOLDER IP65
220V 2P+E 63A**



Industrial > Plugs and sockets > Switched interlocked > Vertical
- with fuse holder > Cee socket outlet, disconnectable (iec
60309) > Ip65 - flush-mount

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Flush-mounted fixed interlocked socket with fuse base. IP65 protection rating. gG type fuses 15x36 mm (not included). Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 15° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 2P+E 63A 200-250V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

| | | | | | |
|---------------------------------|--------------------|----------------------------------|------|---|--------------------------|
| Number of poles | 3 | Degree of protection (IP) | IP65 | Model | Top cover |
| Housing material | Plastic | IEC-ampereage | 63 A | Voltage according to EN 60309-2 | 230 V (50+60 Hz) blue |
| Clock hour position | 6 h | Identification colour | Blue | Contact material | CuZn |
| Surface coating contacts | Untreated | Military model | No | Protection | D0-system |
| Switch | Mechanical locking | With earth leakage switch | No | Empty locations on mounting rail | No |

Barcode



8033954876348

Unit

1 NR

0.295x0.12x0.15 [m]

1.7092 [kg]



8059307217996

Cardboard

10 NR

0.605x0.4x0.35 [m]

17.092 [kg]