

**EC69282**



**MOBILE SOCKET IP44 220V 2P+E 32A**

Industrial > Plugs and sockets > Portable > Sockets > Cee sockets (iec 60309) > Ip44 - 32 a



**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2

**Description**

Industrial mobile socket type EN 60309. IP44 protection degree. Tool-free rapid assembly with 30° twist-lock system. Pre-loosened screw terminals oriented in the same direction for fast wiring. Cable locking nut with gasket. Stainless steel cover springs. 2P+E 32A 200-250V~ 6h

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001320 - CEE coupling (IEC 60309)**

|                                 |           |                                  |          |  |                       |
|---------------------------------|-----------|----------------------------------|----------|--|-----------------------|
| <b>Number of poles</b>          | 3         | <b>Degree of protection (IP)</b> | IP44     | <b>Material</b>                        | Plastic               |
| <b>RAL-number</b>               | 7035      | <b>IEC-amperage</b>              | 32 A     | <b>Voltage according to EN 60309-2</b> | 230 V (50+60 Hz) blue |
| <b>Clock hour position</b>      | 6 h       | <b>Identification colour</b>     | Blue     | <b>Connection system</b>               | Screwed terminal      |
| <b>Cable entry</b>              | Gland nut | <b>Insert direction</b>          | Straight | <b>Contact material</b>                | CuZn                  |
| <b>Surface coating contacts</b> | Untreated | <b>Military model</b>            | No       |  |                       |

**Documentation available for download**

**Certification**

IMQ\_CA02.05870\_2025\_32A.pdf

## Barcode



8033576770550

**Unit**

1 NR

0.245 [kg]



8059307218207

**Pack**

10 NR

0.185x0.295x0.135 [m]

2.45 [kg]



8033576775111

**Cardboard**

60 NR

14.7 [kg]