elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC6929041F

WALL-MOUNT VERT. INTERLOCKED SOCKET WITH FUSE HOLDER IP44 220V 3P+E 16A

Industrial > Plugs and sockets > Switched interlocked > Vertical - with fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip44 - wall-mount

Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II | MADE IN ITALY

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Wall-mounted fixed interlocked socket with fuse base. IP44 protection rating. LED indicator for blown fuse. gG type fuses 10.3x38 mm (not included). Dimensions: 118x277x85 mm. Fixing centers: 141+118x100 mm. 20° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs.
3P+E 16A 200-250V~ 9h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	4	**Degree of protection (IP)**	IP44	**Model**	Base unit and cover
Housing material	Plastic	**IEC-amperage**	16 A	**Voltage according to EN 60309-2**	230 V (50+60 Hz) blue
Clock hour position	9 h	**Identification colour**	Blue	**Contact material**	CuZn
Surface coating contacts	Untreated	**Military model**	No	**Protection**	Cylindrical fuse
Switch	Mechanical locking	**With earth leakage switch**	No	**Empty locations on mounting rail**	No

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

IMQ_CA02.05812_2025_16A_IVCBF.pdf

Barcode

8033954872159

Unit

1 NR

0.295x0.12x0.15 [m]

1.317 [kg]

8059307218337

Cardboard

10 NR

0.605x0.4x0.35 [m]

13.17 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.