



EC6929641F

**WALL-MOUNT VERT. INTERLOCKED
SOCKET WITH FUSE HOLDER IP65
220V 2P+E 32A**



Industrial > Plugs and sockets > Switched interlocked > Vertical
- with fuse holder > Cee socket outlet, disconnectable (iec
60309) > ip65 - wall-mount

Technical Symbols/Marks/Approvals

IP65	IK08	HF	CE	RoHS II	ME	MADE IN ITALY
------	------	----	----	---------	----	---------------

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Wall-mounted fixed interlocked socket with fuse base. IP65 protection rating. LED indicator for blown fuse. gG type fuses 10.3x38 mm (not included). Dimensions: 118x277x85 mm. Fixing centers: 141+118x100 mm. 20° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs.
2P+E 32A 200-250V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	3	Degree of protection (IP)	IP65	Model	Base unit and cover
Housing material	Plastic	IEC-amperage	32 A	Voltage according to EN 60309-2	230 V (50+60 Hz) blue
Clock hour position	6 h	Identification colour	Blue	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	Cylindrical fuse
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	Yes

Documentation available for download



Barcode



8033954872272

Unit

1 NR

0.295x0.12x0.15 [m]

1.317 [kg]



8059307218658

Cardboard

10 NR

0.605x0.4x0.35 [m]

13.17 [kg]