



EC693504



PANEL-MOUNT VERT. INTERLOCKED SOCKET IP65 380V 3P+E 63A

Industrial > Plugs and sockets > Switched interlocked > Vertical
- without fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - flush-mount

Technical Symbols/Marks/Approvals



Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Flush-mounted fixed interlocked socket. IP65 protection rating. Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 15° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 3P+E 63A 380-415V~ 6h

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	4	Degree of protection (IP)	IP65	Model	Top cover
Housing material	Plastic	IEC-amperage	63 A	Voltage according to EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h	Identification colour	Red	Contact material	CuZn
Surface coating contacts	Untreated	Military model	No	Protection	None
Switch	Mechanical locking	With earth leakage switch	No	Empty locations on mounting rail	No

Barcode



8053676576043

Unit

1 NR

0.295x0.12x0.15 [m]

0.72 [kg]



8059307218788

Cardboard

10 NR

0.605x0.4x0.35 [m]

7.2 [kg]