

**EC693514F**

**PANEL-MOUNT VERT. INTERLOCKED SOCKET WITH FUSE HOLDER IP65 380V 3P+N+E 63A**



Industrial > Plugs and sockets > Switched interlocked > Vertical - with fuse holder > Cee socket outlet, disconnectable (iec 60309) > Ip65 - flush-mount

**Technical Symbols/Marks/Approvals**

IP65	IK08	HF	CE	RoHS II		MADE IN ITALY
------	------	----	----	---------	--	---------------

**Norms**

EN 60309-1    EN 60309-2    EN 60309-4

**Description**

Flush-mounted fixed interlocked socket with fuse base. IP65 protection rating. gG type fuses 15x36 mm (not included). Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. 15° angled socket. Switch type: AC23A - 10 kA. Ergonomic handle lockable in ON/OFF position. Stainless steel cover closing springs. 3P+N+E 63A 346-415V~ 6h

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)**

<b>Number of poles</b>	5	<b>Degree of protection (IP)</b>	IP65	<b>Model</b>	Top cover
<b>Housing material</b>	Plastic	<b>IEC-amperage</b>	63 A	<b>Voltage according to EN 60309-2</b>	400 V (50+60 Hz) red
<b>Clock hour position</b>	6 h	<b>Identification colour</b>	Red	<b>Contact material</b>	CuZn
<b>Surface coating contacts</b>	Untreated	<b>Military model</b>	No	<b>Protection</b>	D0-system
<b>Switch</b>	Mechanical locking	<b>With earth leakage switch</b>	No	<b>Empty locations on mounting rail</b>	No

## Barcode



8033954876362

**Unit**

1 NR

0.295x0.12x0.15 [m]

1.7092 [kg]



8059307218870

**Cardboard**

10 NR

0.605x0.4x0.35 [m]

17.092 [kg]