

EC6949241F

WALLL MOUNTING SOCKET WITH FUSE HOLDER SELV 24V 150VA 2P 16A

Industrial > Plugs and sockets > Switched interlocked > Vertical - low voltage > Cee socket outlet, disconnectable (iec 60309) > Wall-mount

Technical Symbols/Marks/Approvals

IP44 | IK08 | HF | CE | RoHS II | MADE IN ITALY

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Wall-mounted fixed socket with safety transformer 220-24V~ 150 VA. IP44 protection rating. Dimensions: 118x277x85 mm. Straight socket. With voltage presence indicator light. With primary+secondary fuse base type gG 10.3x38 mm (fuses not included). LED indicator for blown fuse on the primary circuit. Stainless steel cover closing springs.
2P 16A 24V~ 150VA

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	2	**Degree of protection (IP)**	IP44	**Model**	Base unit and cover
Housing material	Plastic	**IEC-amperage**	16 A	**Voltage according to EN 60309-2**	20-25 V (50+60 Hz) violet
Identification colour	Purple	**Contact material**	CuZn	**Surface coating contacts**	Untreated
Military model	No	**Protection**	Cylindrical fuse	**Switch**	Without on/off switch
With earth leakage switch	No	**Empty locations on mounting rail**	No		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8033954872340
Unit
1 NR
0.295x0.12x0.15 [m]
2.264 [kg]

8059307219129
Cardboard
10 NR
0.605x0.4x0.35 [m]
22.64 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.