

**EC694924F**



**PANEL-MOUNT SOCKET WITH FUSE HOLDER SELV 24V 150VA 2P 16A**

Industrial > Plugs and sockets > Switched interlocked > Vertical - low voltage > Cee socket outlet, disconnectable (iec 60309) > Flush-mount

**Technical Symbols/Marks/Approvals**



**Norms**

EN 60309-1 EN 60309-2 EN 60309-4

**Description**

Flush-mounted fixed socket with safety transformer 220-24V~ 150 VA. IP44 protection rating. Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. Straight socket. With voltage presence indicator light. With primary+secondary fuse base type gG 10.3x38 mm (fuses not included). LED indicator for blown fuse on the primary circuit. Stainless steel cover closing springs. 2P 16A 24V~ 150VA

**Etim**

**GROUP EG000014 - Industrial sockets/plug applications**

**CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)**

<b>Number of poles</b>	2	<b>Degree of protection (IP)</b>	IP44	<b>Model</b>	Top cover
<b>Housing material</b>	Plastic	<b>IEC-amperage</b>	16 A	<b>Voltage according to EN 60309-2</b>	20-25 V (50+60 Hz) violet
<b>Identification colour</b>	Purple	<b>Contact material</b>	CuZn	<b>Surface coating contacts</b>	Untreated
<b>Military model</b>	No	<b>Protection</b>	Cylindrical fuse	<b>Switch</b>	Without on/off switch
<b>With earth leakage switch</b>	No	<b>Empty locations on mounting rail</b>	No		

## Barcode



8033954872333

**Unit**

1 NR

0.295x0.12x0.15 [m]

2.02 [kg]



8059307219136

**Cardboard**

10 NR

0.605x0.4x0.35 [m]

20.2 [kg]