

EC694924F



**PANEL-MOUNT SOCKET WITH FUSE HOLDER SELV
24V 150VA 2P 16A**

Industrial > Plugs and sockets > Switched interlocked > Vertical - low voltage > Cee socket outlet, disconnectable (iec 60309) > Flush-mount

Technical Symbols/Marks/Approvals

IP44	IK08	HF	CE	RoHS II		MADE IN ITALY
------	------	----	----	---------	--	---------------

Norms

EN 60309-1 EN 60309-2 EN 60309-4

Description

Flush-mounted fixed socket with safety transformer 220-24V~ 150 VA. IP44 protection rating. Dimensions: 118x277x20 mm. Fixing centers: 141+118x100 mm. Straight socket. With voltage presence indicator light. With primary+secondary fuse base type gG 10.3x38 mm (fuses not included). LED indicator for blown fuse on the primary circuit. Stainless steel cover closing springs. 2P 16A 24V~ 150VA

Etim

GROUP EG000014 - Industrial sockets/plug applications

CLASS EC001324 - CEE socket outlet, disconnectable, with fuse (IEC 60309)

Number of poles	2	Degree of protection (IP)	IP44	Model	Top cover
Housing material	Plastic	IEC-amperage	16 A	Voltage according to EN 60309-2	20-25 V (50+60 Hz) violet
Identification colour	Purple	Contact material	CuZn	Surface coating contacts	Untreated
Military model	No	Protection	Cylindrical fuse	Switch	Without on/off switch
With earth leakage switch	No	Empty locations on mounting rail	No		

Barcode



8033954872333

Unit

1 NR

0.295x0.12x0.15 [m]

2.02 [kg]



8059307219136

Cardboard

10 NR

0.605x0.4x0.35 [m]

20.2 [kg]