

EC6992020

CABLE REEL 2 SCHUKO/ITALIAN - 30 m

Industrial > Cable reels and extension cords > Cable reels and extension cords > Cable reel > Cable reel > 2 domestic sockets - 20/30 meters cable h07rn-f

Technical Symbols/Marks/Approvals

IP44 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 61242 EN 61316

Description

Cable reel with galvanized and painted metal stand. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum featuring an automatic braking system and anti-snap cable clip. Resettable thermal cutout (>55 °C). Rewind handle.
Drum diameter: 330 mm. Dimensions: 230x335x410 mm.
2 Sockets: 10/16A 2P 220V~ Schuko/Bivalent (P40) IP55
Cable: H07RN-F - 3G2.5 - 30 m
Plug: 16A 2P+E 220V~ CEE plug IP44

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG020002 - Accessories for power tools

CLASS EC000191 - Cable reel

Degree of protection (IP)	IP44	**Colour**	Grey	**Type of fastening**	None
Housing material	Plastic	**Number of cores**	3	**Cable assembly**	H07RN-F
Core cross section	2.5 mm²	**Number of CEE socket outlets (IEC 60309)**	0	**Number of socket outlets with protective contact CEE 7/3 (type F)**	2
Number of socket outlets British Standard BS 1363	0	**Number of socket outlets British standard**	0	**Number of socket outlets Italian standard type Bipasso**	2
Number of socket outlets Italian standard type P11	0	**Number of socket outlets Italian standard type P17**	0	**Number of socket outlets Italian standard type P30**	0
Number of universal multi standard sockets	0	**Number of socket outlets Swiss standard type 13**	0	**Number of socket outlets Swiss standard type 15**	0
Number of socket outlets Swiss standard type 23	0	**Number of socket outlets Swiss standard type 25**	0	**Type of mains connection**	CEE
Cable length	30 m	**With mounting frame**	Yes	**Automatic cable winding**	No
With thermal overload protection	Yes	**With locking**	No	**With lamp**	No
With charging cable for E-Mobility	No	**Earthing cable reel**	No	**Protection**	Overcurrent switch

Technical Characteristics

Power cable coiled	1.8 kW	**Power cable unwound**	3.6 kW	**Prese_16A_2P+T**	-
Prese_16A_3P+N+T	-	**Prese_16A_3P+T**	-	**Installed sockets 10/16A 2P+E**	-
Installed sockets type	Schuko / Bivalente	**Schuko/bivalent sockets**	2	**EN 60309 16A plug**	2P+T

Barcode

8033576779522

Unit

1 NR

0.43x0.255x0.54 [m]

9 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.