

## EC6992020



### CABLE REEL 2 SCHUKO/ITALIAN - 30 m



Industrial > Cable reels and extension cords > Cable reels and extension cords > Cable reel > Cable reel > 2 domestic sockets - 20/30 meters cable h07rn-f

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61242 EN 61316

### Description

Cable reel with galvanized and painted metal stand. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum featuring an automatic braking system and anti-snap cable clip. Resettable thermal cutout (>55 °C). Rewind handle. Drum diameter: 330 mm. Dimensions: 230x335x410 mm.  
2 Sockets: 10/16A 2P 220V~ Schuko/Bivalent (P40) IP55  
Cable: H07RN-F - 3G2.5 - 30 m  
Plug: 16A 2P+E 220V~ CEE plug IP44

## Etim

### GROUP EG020002 - Accessories for power tools

#### CLASS EC000191 - Cable reel

<b>Degree of protection (IP)</b>	IP44	<b>Colour</b>	Grey	<b>Type of fastening</b>	None
<b>Housing material</b>	Plastic	<b>Number of cores</b>	3	<b>Cable assembly</b>	H07RN-F
<b>Core cross section</b>	2.5 mm <sup>2</sup>	<b>Number of CEE socket outlets (IEC 60309)</b>	0	<b>Number of socket outlets with protective contact CEE 7/3 (type F)</b>	2
<b>Number of socket outlets British Standard BS 1363</b>	0	<b>Number of socket outlets British standard</b>	0	<b>Number of socket outlets Italian standard type Bipasso</b>	2
<b>Number of socket outlets Italian standard type P11</b>	0	<b>Number of socket outlets Italian standard type P17</b>	0	<b>Number of socket outlets Italian standard type P30</b>	0
<b>Number of universal multi standard sockets</b>	0	<b>Number of socket outlets Swiss standard type 13</b>	0	<b>Number of socket outlets Swiss standard type 15</b>	0
<b>Number of socket outlets Swiss standard type 23</b>	0	<b>Number of socket outlets Swiss standard type 25</b>	0	<b>Type of mains connection</b>	CEE
<b>Cable length</b>	30 m	<b>With mounting frame</b>	Yes	<b>Automatic cable winding</b>	No
<b>With thermal overload protection</b>	Yes	<b>With locking</b>	No	<b>With lamp</b>	No
<b>With charging cable for E-Mobility</b>	No	<b>Earthing cable reel</b>	No	<b>Protection</b>	Overcurrent switch

## Technical Characteristics

<b>Power cable coiled</b>	1.8 kW	<b>Power cable unwound</b>	3.6 kW	<b>Prese_16A_2P+T</b>	-
<b>Prese_16A_3P+N+T</b>	-	<b>Prese_16A_3P+T</b>	-	<b>Installed sockets 10/16A 2P+E</b>	-
<b>Installed sockets type</b>	Schuko / Bivalente	<b>Schuko/bivalent sockets</b>	2	<b>EN 60309 16A plug</b>	2P+T

## Barcode



8033576779522

**Unit**

1 NR

0.43x0.255x0.54 [m]

9 [kg]