

EC6992120



CABLE REEL 1X2P+E+1X3P+E-20 m - 5X2,5

Industrial > Cable reels and extension cords > Cable reels and extension cords > Cable reel > Cable reel > 2 sockets - 20 meters cable h07rn-f



Technical Symbols/Marks/Approvals



Norms

EN 61242 EN 61316

Description

Cable reel with galvanized and painted metal support. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum with automatic braking system and anti-tear cable clamp. Resettable thermal cutout >55 °C. Manual rewind handle. Drum diameter 330 mm. Dimensions 230x335x410 mm.

1 CEE 16A 2P+E 220V~ IP44 socket

1 CEE 16A 3P+E 380V~ IP44 socket

H07RN-F cable - 5G2.5 - 20 m

CEE 16A 3P+N+E 380V~ IP44 plug

Etim

GROUP EG020002 - Accessories for power tools

CLASS EC000191 - Cable reel

| | | | | | |
|---|---------------------|---|------|--|--------------------|
| Degree of protection (IP) | IP44 | Colour | Grey | Type of fastening | None |
| Housing material | Plastic | Number of cores | 5 | Cable assembly | H07RN-F |
| Core cross section | 2.5 mm ² | Number of CEE socket outlets (IEC 60309) | 2 | Number of socket outlets with protective contact CEE 7/3 (type F) | 0 |
| Number of socket outlets British Standard BS 1363 | 0 | Number of socket outlets British standard | 0 | Number of socket outlets Italian standard type Bipasso | 0 |
| Number of socket outlets Italian standard type P11 | 0 | Number of socket outlets Italian standard type P17 | 0 | Number of socket outlets Italian standard type P30 | 0 |
| Number of universal multi standard sockets | 0 | Number of socket outlets Swiss standard type 13 | 0 | Number of socket outlets Swiss standard type 15 | 0 |
| Number of socket outlets Swiss standard type 23 | 0 | Number of socket outlets Swiss standard type 25 | 0 | Type of mains connection | CEE |
| Cable length | 20 m | With mounting frame | Yes | Automatic cable winding | No |
| With thermal overload protection | Yes | With locking | No | With lamp | No |
| With charging cable for E-Mobility | No | Earthing cable reel | No | Protection | Overcurrent switch |

Technical Characteristics

| | | | | | |
|---------------------------|--------|----------------------------|---------|--------------------------------|---|
| Power cable coiled | 5 kW | Power cable unwound | 11.0 kW | Prese_16A_2P+T | 1 |
| Prese_16A_3P+N+T | - | Prese_16A_3P+T | 1 | Schuko/bivalent sockets | - |
| EN 60309 16A plug | 3P+N+T | | | | |

Barcode



8033576779560

Unit

1 NR

0.43x0.255x0.54 [m]

9.37 [kg]