



EC6992131

CABLE REEL 2X2P+E-30 m - 3X2,5

Industrial > Cable reels and extension cords > Cable reels and extension cords > Cable reel > Cable reel > 2 sockets - 30 meters cable h07rn-f



Technical Symbols/Marks/Approvals



Norms

EN 61242 EN 61316

Description

Cable reel with galvanized and painted metal support. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum with automatic braking system and anti-tear cable clamp. Resettable thermal cutout >55 °C. Manual rewind handle. Drum diameter 330 mm. Dimensions 230x335x410 mm.
2 CEE 16A 2P+E 220V~ IP67 sockets
H07RN-F cable - 3G2.5 - 30 m
CEE 16A 2P+E 220V~ IP67 plug

Etim

GROUP EG020002 - Accessories for power tools


CLASS EC000191 - Cable reel

Degree of protection (IP)	IP55	Colour	Grey	Type of fastening	None
Housing material	Plastic	Number of cores	3	Cable assembly	H07RN-F
Core cross section	2.5 mm ²	Number of CEE socket outlets (IEC 60309)	2	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets British Standard BS 1363	0	Number of socket outlets British standard	0	Number of socket outlets Italian standard type Bipasso	0
Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0
Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE
Cable length	30 m	With mounting frame	Yes	Automatic cable winding	No
With thermal overload protection	Yes	With locking	No	With lamp	No
With charging cable for E-Mobility	No	Earthing cable reel	No	Protection	Overcurrent switch

Technical Characteristics

Power cable coiled	1.8 kW	Power cable uncoiled	3.6 kW	Prese_16A_2P+T	2
Prese_16A_3P+N+T	-	Prese_16A_3P+T	-	Schuko/bivalent sockets	-
EN 60309 16A plug	2P+T				

Barcode



8033576779669

Unit

1 NR

0.43x0.255x0.54 [m]

9 [kg]