

EC6992325



CABLE REEL 4X3P+E - 4X2,5 - IP44 - 30 m

Industrial > Cable reels and extension cords > Cable reels and extension cords > Cable reel > Cable reel > 4 sockets - 30 meters cable h07rn-f



Technical Symbols/Marks/Approvals



Norms

EN 61242 EN 61316

Description

Cable reel with galvanized and painted metal support. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum with automatic braking system and anti-tear cable clamp. Resettable thermal cutout >55 °C. Manual rewind handle. Drum diameter 400 mm. Dimensions 235x410x530 mm.
4 CEE 16A 3P+E 380V~ IP44 sockets
H07RN-F cable - 4G2.5 - 30 m
CEE 16A 3P+E 380V~ IP44 plug

Etim

GROUP EG020002 - Accessories for power tools


CLASS EC000191 - Cable reel

Degree of protection (IP)	IP44	Colour	Grey	Type of fastening	None
Housing material	Plastic	Number of cores	4	Cable assembly	H07RN-F
Core cross section	2.5 mm ²	Number of CEE socket outlets (IEC 60309)	4	Number of socket outlets with protective contact CEE 7/3 (type F)	0
Number of socket outlets British Standard BS 1363	0	Number of socket outlets British standard	0	Number of socket outlets Italian standard type P11	0
Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0	Number of universal multi standard sockets	0
Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0	Number of socket outlets Swiss standard type 23	0
Number of socket outlets Swiss standard type 25	0	Type of mains connection	CEE	Cable length	30 m
With mounting frame	Yes	Automatic cable winding	No	With thermal overload protection	Yes
With locking	No	With lamp	No	With charging cable for E-Mobility	No
Earthing cable reel	No	Protection	Overcurrent switch		

Technical Characteristics

Power cable coiled	4.5 kW	Power cable unwound	11.0 kW	Prese_16A_2P+T	-
Prese_16A_3P+N+T	-	Prese_16A_3P+T	4	Schuko/bivalent sockets	-
EN 60309 16A plug	3P+T				

Barcode



8033576779744

Unit

1 NR

0.43x0.255x0.54 [m]

12 [kg]