

EC6992334

CABLE REEL 4X2P+E - 3X2,5 - IP65 - 30 m

Industrial > Cable reels and extension cords > Cable reels and extension cords > Cable reel > Cable reel > 4 sockets - 30 meters cable h07rn-f



Technical Symbols/Marks/Approvals



Norms

EN 61242 EN 61316

Description

Cable reel with galvanized and painted metal support. Soft-grip carrying handle. Rated voltage 230/400V~ - 50 Hz. Insulation voltage 500/690V~. Drum with automatic braking system and anti-tear cable clamp. Resettable thermal cutout >55 °C. Manual rewind handle. Drum diameter 400 mm. Dimensions 235x410x530 mm.
4 CEE 16A 2P+E 220V~ IP67 sockets
H07RN-F cable - 3G2.5 - 30 m
CEE 16A 2P+E 220V~ IP67 plug

Etim

GROUP EG020002 - Accessories for power tools


CLASS EC000191 - Cable reel

| | | | | | |
|--|---------------------|--|--------------------|---|---------|
| Degree of protection (IP) | IP55 | Colour | Grey | Type of fastening | None |
| Housing material | Plastic | Number of cores | 3 | Cable assembly | H07RN-F |
| Core cross section | 2.5 mm ² | Number of CEE socket outlets (IEC 60309) | 4 | Number of socket outlets with protective contact CEE 7/3 (type F) | 0 |
| Number of socket outlets British Standard BS 1363 | 0 | Number of socket outlets British standard | 0 | Number of socket outlets Italian standard type P11 | 0 |
| Number of socket outlets Italian standard type P17 | 0 | Number of socket outlets Italian standard type P30 | 0 | Number of universal multi standard sockets | 0 |
| Number of socket outlets Swiss standard type 13 | 0 | Number of socket outlets Swiss standard type 15 | 0 | Number of socket outlets Swiss standard type 23 | 0 |
| Number of socket outlets Swiss standard type 25 | 0 | Type of mains connection | CEE | Cable length | 30 m |
| With mounting frame | Yes | Automatic cable winding | No | With thermal overload protection | Yes |
| With locking | No | With lamp | No | With charging cable for E-Mobility | No |
| Earthing cable reel | No | Protection | Overcurrent switch | | |

Technical Characteristics

| | | | | | |
|--------------------|--------|---------------------|--------|-------------------------|---|
| Power cable coiled | 1.8 kW | Power cable unwound | 3.6 kW | Prese_16A_2P+T | 4 |
| Prese_16A_3P+N+T | - | Prese_16A_3P+T | - | Schuko/bivalent sockets | - |
| EN 60309 16A plug | 2P+T | | | | |

Barcode



8033576779805

Unit

1 NR

0.43x0.255x0.54 [m]

10.2 [kg]