

EC70025



**JOINT PIPE-BOX IP67 Ø25 mm - GREY
- EASYSYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Easy system - ip67 fittings > Coupler conduit - box



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals

IP67	UL94 V0	GWT 960°	IK07	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	--	---------------

Norms

EN 61386-1 EN 61386-21

Description

Fitting for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP67 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Metric thread pitch 1.5 mm. Supplied with pre-mounted gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards. Diameter 20 mm - Length 47 mm - Thread length 15 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)
CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	25-25 mm	Suitable for built-in installation box	No	Suitable for junction box	Yes
Suitable for cable box	Yes	Suitable for expansion ring	No	For tube diameter	25 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	47 mm	thread length	15 mm
--------	-------	---------------	-------

Documentation available for download



Barcode



8050880883585

Pack

25 NR

0.5625 [kg]



8057711591282

Cardboard

400 NR

0.39x0.295x0.3 [m]

9 [kg]