



EC70025CR

JOINT PIPE-BOX IP67 Ø25 mm - RED RAL3000 - EASYSYSTEM



Enclosures > Special application systems > Emergency line >
Conduits and fittings > Coupler conduit - box

Technical Symbols/Marks/Approvals

IP67	UL94 V0	GWT 960°	IK07	CE	RoHS II	MADE IN ITALY
------	------------	-------------	------	----	---------	---------------------

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-box connector made of impact-resistant rigid PVC-based technopolymer. Soft internal sealing ring for conduit tolerance compensation. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread. Supplied with gasket and fixing locknut mounted. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.

Diameter 25 mm - Length 47 mm - Thread length 15 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	25-25 mm	Suitable for built-in installation box	No	Suitable for junction box	Yes
Suitable for cable box	Yes	Suitable for expansion ring	No	For tube diameter	25 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	47 mm	thread length	15 mm
--------	-------	---------------	-------

Barcode



8056351664097

Pack

25 NR

0.5625 [kg]



8056351663854

Cardboard

400 NR

0.295x0.39x0.3 [m]

9 [kg]