elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

EC70032

JOINT PIPE-BOX IP67 Ø32 mm - GREY - EASYSYSTEM

Conduits and fittings > Accessories and fittings > Joints and fittings > Easy system - ip67 fittings > Coupler conduit - box

Technical Symbols/Marks/Approvals

IP67 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Fitting for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP67 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Metric thread pitch 1.5 mm. Supplied with pre-mounted gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 32 mm - Length 52 mm - Thread length 16 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	32-32 mm	**Suitable for built-in installation box**	No	**Suitable for junction box**	Yes
Suitable for cable box	Yes	**Suitable for expansion ring**	No	**For tube diameter**	32 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	52 mm	**thread length**	16 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Raccordi Easy system_2023.pdf

Barcode

8050880883592

Pack

25 NR

0.875 [kg]

8057711591299

Cardboard

200 NR

0.39x0.295x0.3 [m]

7 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.