

**EC72025**



**JOINT PIPE-SPIRAL CONDUIT IP65  
Ø25 mm - GREY - EASYSYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Easy system - ip67 fittings > Coupler conduit - spiral conduit



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

IP67	UL94 V0	GWT 960°	IK07	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	--	---------------

**Norms**

EN 61386-1 EN 61386-21

**Description**

Fitting for the connection between a pipe and a spiral conduit of the same diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP67 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.  
Diameter 25 mm

**Etim**

**GROUP EG000003 - Protective hose systems**  
**CLASS EC001172 - Coupler for corrugated plastic hoses**

<b>Degree of protection (IP)</b>	IP67	<b>Material</b>	Plastic	<b>Material quality</b>	Other
<b>Colour</b>	Grey	<b>Model</b>	Straight	<b>Working temperature</b>	-5-60 °C
<b>Nominal size</b>	25-25 mm				

**Documentation available for download**



**Certification**

Raccordi Easy system\_2023.pdf

## Barcode



8050880883707

**Pack**

25 NR

0.6825 [kg]



8057711591404

**Cardboard**

300 NR

0.39x0.295x0.3 [m]

8.19 [kg]