

**EC73016**



**BEND 90° IP67 Ø16 mm - GREY - EASYSYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Easy system - ip67 fittings > Coupler bend conduit - conduit



**Technical Symbols/Marks/Approvals**

IP67	UL94 V0	GWT 960°	IK07	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	--	---------------

**Norms**

EN 61386-1 EN 61386-21

**Description**

90° bend for the connection between two pipes of the same diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP67 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 16 mm - Bending radius 56 mm

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC000936 - Bend for installation tubes**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Surface protection</b>	Untreated	<b>Colour</b>	Grey	<b>Model</b>	Plug-in
<b>Diameter</b>	16 mm	<b>Flexible</b>	No	<b>UV resistant</b>	Yes
<b>Quality of surface coating</b>	Uncoated	<b>Surface polished</b>	No	<b>Surface brushed</b>	No
<b>Compressive strength class according to EN 61386-1</b>	None	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>For nominal tube diameter</b>	16 mm
<b>With sleeve</b>	Yes	<b>Two-part</b>	No	<b>With inspection opening and cover</b>	No
<b>Radius</b>	56 mm	<b>Bend angle</b>	90 °		

## Documentation available for download



## Barcode



8050880883745

**Pack**

25 NR

0.6175 [kg]



8057711591442

**Cardboard**

300 NR

0.39x0.295x0.3 [m]

7.41 [kg]