

**EC73025CR**



**BEND 90° IP67 Ø25 mm - RED RAL3000  
- EASYSYSTEM**



Enclosures > Special application systems > Emergency line >  
Conduits and fittings > Coupler bend conduit - conduit

**Technical Symbols/Marks/Approvals**

IP67	UL94 V0	GWT 960°	IK07	CE	RoHS II	MADE IN ITALY
------	------------	-------------	------	----	---------	---------------------

**Norms**

EN 61386-1 EN 61386-21

**Description**

90° conduit-to-conduit bend for connecting two pipes of the same diameter, made of impact-resistant rigid PVC-based technopolymer. Soft internal sealing ring for conduit tolerance compensation. IP67 protection degree. Self-extinguishing grade V0 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.

Diameter 25 mm - bending radius 70 mm

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC000936 - Bend for installation tubes**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Surface protection</b>	Untreated	<b>Colour</b>	Other	<b>Model</b>	Plug-in
<b>Diameter</b>	25 mm	<b>Flexible</b>	No	<b>UV resistant</b>	Yes
<b>Quality of surface coating</b>	Uncoated	<b>Surface polished</b>	No	<b>Surface brushed</b>	No
<b>Compressive strength class according to EN 61386-1</b>	None	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>For nominal tube diameter</b>	25 mm
<b>With sleeve</b>	Yes	<b>Two-part</b>	No	<b>With inspection opening and cover</b>	No
<b>Radius</b>	88 mm	<b>Bend angle</b>	90 °		

## Barcode



8056351664110

**Pack**

25 NR

1.3 [kg]



8056351663878

**Cardboard**

100 NR

0.295x0.39x0.3 [m]

5.2 [kg]