

EC73025CR



**BEND 90° IP67 Ø25 mm - RED RAL3000
- EASYSYSTEM**

Enclosures > Special application systems > Emergency line >
Conduits and fittings > Coupler bend conduit - conduit



Technical Symbols/Marks/Approvals

IP67	UL94 V0	GWT 960°	IK07	CE	RoHS II	MADE IN ITALY
------	------------	-------------	------	----	---------	---------------------

Norms

EN 61386-1 EN 61386-21

Description

90° conduit-to-conduit bend for connecting two pipes of the same diameter, made of impact-resistant rigid PVC-based technopolymer. Soft internal sealing ring for conduit tolerance compensation. IP67 protection degree. Self-extinguishing grade V0 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.

Diameter 25 mm - bending radius 70 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	Material quality	Polyvinyl chloride (PVC)	Halogen free	No
Surface protection	Untreated	Colour	Other	Model	Plug-in
Diameter	25 mm	Flexible	No	UV resistant	Yes
Quality of surface coating	Uncoated	Surface polished	No	Surface brushed	No
Compressive strength class according to EN 61386-1	None	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	For nominal tube diameter	25 mm
With sleeve	Yes	Two-part	No	With inspection opening and cover	No
Radius	88 mm	Bend angle	90 °		

Barcode



8056351664110

Pack

25 NR

1.3 [kg]



8056351663878

Cardboard

100 NR

0.295x0.39x0.3 [m]

5.2 [kg]