

**EC74032**



**JOINT PIPE-PIPE IP67 Ø32 mm - GREY  
- SECURITY**

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Joint conduit - conduit



**Technical Symbols/Marks/Approvals**

|      |    |             |      |    |         |  |                     |
|------|----|-------------|------|----|---------|--|---------------------|
| IP67 | HF | GWT<br>850° | IK07 | CE | RoHS II |  | MADE<br>IN<br>ITALY |
|------|----|-------------|------|----|---------|--|---------------------|

**Norms**

EN 61386-1 EN 61386-21

**Description**

Conduit-to-conduit coupling for connecting two pipes of the same diameter, made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards. Diameter 32 mm - Length 82 mm

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC000939 - Coupler for installation tubes**

|  |           |                                   |                   |                         |         |
|--|-----------|-----------------------------------|-------------------|-------------------------|---------|
| <b>Material</b>                          | Plastic   | <b>Material quality</b>           | Polyethylene (PE) | <b>Halogen free</b>     | Yes     |
| <b>Surface protection</b>                | Untreated | <b>Colour</b>                     | Grey              | <b>Model</b>            | Plug-in |
| <b>UV resistant</b>                      | Yes       | <b>Quality of surface coating</b> | Uncoated          | <b>Surface polished</b> | No      |
| <b>Surface brushed</b>                   | No        | <b>For nominal tube diameter</b>  | 32 mm             | <b>Two-part</b>         | No      |
| <b>With inspection opening and cover</b> | No        | <b>With lock function</b>         | No                | <b>Material sealing</b> | Rubber  |
| <b>With outer thread</b>                 | No        | <b>With inner thread</b>          | No                | <b>Separable</b>        | No      |
| <b>Eccentric</b>                         | No        |                                   |                   |                         |         |

**Technical Characteristics**

length 82 mm

## Documentation available for download



## Barcode



8050880883837

**Pack**

10 NR

0.233 [kg]



8057711591527

**Cardboard**

100 NR

0.295x0.39x0.21 [m]

2.33 [kg]