

EC74140



**JOINT PIPE-BOX IP67 Ø40 mm - GREY
- SECURITY**

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler conduit - box

Technical Symbols/Marks/Approvals

IP67	HF	GWT 850°	IK07	CE	RoHS II		MADE IN ITALY
------	----	----------	------	----	---------	--	---------------

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-box connector made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. 1.5 mm metric pitch thread. Supplied with gasket and fixing locknut mounted. Manufactured in compliance with EN 61386-1, EN 61386-21 standards. Diameter 40 mm - Length 75 mm - Thread length 17 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)
CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	40-40 mm	Suitable for built-in installation box	No	Suitable for junction box	Yes
Suitable for cable box	Yes	Suitable for expansion ring	No	For tube diameter	40 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	75 mm	thread length	17 mm
--------	-------	---------------	-------

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Barcode



8050880883905

Pack

5 NR

0.208 [kg]



8057711591596

Cardboard

80 NR

0.295x0.39x0.21 [m]

3.328 [kg]