

EC74150

JOINT PIPE-BOX IP67 Ø50 mm - GREY - SECURITY

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler conduit - box

Technical Symbols/Marks/Approvals

IP67 | HF | GWT 850° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-box connector made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. 1.5 mm metric pitch thread. Supplied with gasket and fixing locknut mounted. Manufactured in compliance with EN 61386-1, EN 61386-21 standards. Diameter 50 mm - Length 75 mm - Thread length 17 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	50-50 mm	**Suitable for built-in installation box**	No	**Suitable for junction box**	Yes
Suitable for cable box	Yes	**Suitable for expansion ring**	No	**For tube diameter**	Other
Number of conduit lead-ins	1				

Technical Characteristics

length	75 mm	**thread length**	17 mm

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880883912

Pack

5 NR

0.28 [kg]



8057711591602

Cardboard

40 NR

0.295x0.39x0.21 [m]

2.24 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.