

EC74216

JOINT PIPE-SPIRAL CONDUIT IP65 Ø16 mm - GREY - SECURITY

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler conduit - spiral conduit

Technical Symbols/Marks/Approvals

IP67 | HF | GWT 850° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-spiral-conduit connector for connecting a pipe and a spiral conduit of the same diameter, made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 16 mm

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001172 - Coupler for corrugated plastic hoses

Degree of protection (IP)	IP67	**Material**	Plastic	**Material quality**	Other
Colour	Grey	**Model**	Straight	**Working temperature**	-5-60 °C
Nominal size	16-16 mm				

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880883929

Pack

10 NR

0.075 [kg]



8057711591619

Cardboard

350 NR

0.295x0.39x0.21 [m]

2.625 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.