

EC74225



**JOINT PIPE-SPIRAL CONDUIT IP65
Ø25 mm - GREY - SECURITY**

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler conduit - spiral conduit



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

Conduit-to-spiral-conduit connector for connecting a pipe and a spiral conduit of the same diameter, made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 25 mm

Etim

GROUP EG000003 - Protective hose systems
CLASS EC001172 - Coupler for corrugated plastic hoses

| | | | | | |
|----------------------------------|----------|-----------------|----------|----------------------------|----------|
| Degree of protection (IP) | IP67 | Material | Plastic | Material quality | Other |
| Colour | Grey | Model | Straight | Working temperature | -5-60 °C |
| Nominal size | 25-25 mm | | | | |

Documentation available for download



Barcode



8050880883943

Pack

10 NR

0.136 [kg]



8057711591633

Cardboard

200 NR

0.295x0.39x0.21 [m]

2.72 [kg]