

EC74320

BEND 90° IP67 Ø20 mm - GREY - SECURITY

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler bend conduit - conduit

Technical Symbols/Marks/Approvals

IP67 | HF | GWT 850° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

90° conduit-to-conduit bend for connecting two pipes of the same diameter, made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards.
Diameter 20 mm - bending radius 100 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyethylene (PE)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	20 mm	**Flexible**	No	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	20 mm
With sleeve	Yes	**Two-part**	No	**With inspection opening and cover**	No
Radius	100 mm	**Bend angle**	90 °		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Raccordi Security System_2023.pdf

Barcode

8050880883998

Pack

10 NR

0.228 [kg]

8057711591688

Cardboard

100 NR

0.295x0.39x0.21 [m]

2.28 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.