

EC74332



BEND 90° IP67 Ø32 mm - GREY - SECURITY

Conduits and fittings > Accessories and fittings > Joints and fittings > Security system - ip67 fittings > Coupler bend conduit - conduit



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

90° conduit-to-conduit bend for connecting two pipes of the same diameter, made of co-molded impact-resistant and low-smoke emission technopolymers. IP67 protection degree. Self-extinguishing grade V2 according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 850 °C. Manufactured in compliance with EN 61386-1, EN 61386-21 standards. Diameter 32 mm - bending radius 100 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	Material quality	Polyethylene (PE)	Halogen free	Yes
Surface protection	Untreated	Colour	Grey	Model	Plug-in
Diameter	32 mm	Flexible	No	UV resistant	Yes
Quality of surface coating	Uncoated	Surface polished	No	Surface brushed	No
Compressive strength class according to EN 61386-1	None	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	For nominal tube diameter	32 mm
With sleeve	Yes	Two-part	No	With inspection opening and cover	No
Radius	100 mm	Bend angle	90 °		

Documentation available for download



Barcode



8050880884018

Pack

10 NR

0.424 [kg]



8057711591701

Cardboard

50 NR

0.295x0.39x0.21 [m]

2.12 [kg]