elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC75025

JOINT PIPE-BOX IP65 Ø25 mm - GREY - SPEED SYSTEM

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit-box > Coupler conduit-box

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread, supplied with pre-assembled gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 25 mm - Length 55 mm - Thread length 14 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)

CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	25-25 mm	**Suitable for built-in installation box**	No	**Suitable for junction box**	Yes
Suitable for cable box	Yes	**Suitable for expansion ring**	No	**For tube diameter**	25 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	55 mm	**thread length**	14 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Raccordi IP65_EM182_2023.pdf

Barcode

8050507871865

Pack

10 NR

0.225 [kg]

8050507871872

Cardboard

200 NR

0.39x0.295x0.21 [m]

4.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.