

EC75025



**JOINT PIPE-BOX IP65 Ø25 mm - GREY
- SPEED SYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit-box > Coupler conduit-box



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread, supplied with pre-assembled gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards. Diameter 25 mm - Length 55 mm - Thread length 14 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)
CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	25-25 mm	Suitable for built-in installation box	No	Suitable for junction box	Yes
Suitable for cable box	Yes	Suitable for expansion ring	No	For tube diameter	25 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	55 mm	thread length	14 mm
---------------	-------	----------------------	-------

Documentation available for download



Barcode



8050507871865

Pack

10 NR

0.225 [kg]



8050507871872

Cardboard

200 NR

0.39x0.295x0.21 [m]

4.5 [kg]