

EC75032



**JOINT PIPE-BOX IP65 Ø32 mm - GREY
- SPEED SYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit-box > Coupler conduit-box



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread, supplied with pre-assembled gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards. Diameter 32 mm - Length 65 mm - Thread length 14 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)
CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	32-32 mm	Suitable for built-in installation box	No	Suitable for junction box	Yes
Suitable for cable box	Yes	Suitable for expansion ring	No	For tube diameter	32 mm
Number of conduit lead-ins	1				

Technical Characteristics

length	65 mm	thread length	14 mm
---------------	-------	----------------------	-------

Documentation available for download



Certification
Raccordi
IP65_EM182_2023.
pdf

Barcode



8050507871889
Pack
10 NR
0.368 [kg]



8050507871896
Cardboard
100 NR
0.39x0.295x0.21 [m]
3.68 [kg]