

EC75050



**JOINT PIPE-BOX IP65 Ø50 mm - GREY
- SPEED SYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit-box > Coupler conduit-box



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a junction box, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. 1.5 mm metric pitch thread, supplied with pre-assembled gasket and locknut. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards. Diameter 50 mm - Length 80 mm - Thread length 20 mm

Etim

GROUP EG000048 - Connection material (electrotechnical)
CLASS EC002326 - Cable plug for cable-/installation tube entry

Suitable for cable diameter	50-50 mm	Suitable for built-in installation box	No	Suitable for junction box	Yes
Suitable for cable box	Yes	Suitable for expansion ring	No	For tube diameter	Other
Number of conduit lead-ins	1				

Technical Characteristics

length	80 mm	thread length	20 mm
---------------	-------	----------------------	-------

Documentation available for download



Barcode



8050507871926

Pack

5 NR

0.339 [kg]



8050507871933

Cardboard

40 NR

0.39x0.295x0.21 [m]

2.712 [kg]