elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC75116

JOINT PIPE-PIPE IP65 Ø16 mm - GREY - SPEED SYSTEM

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Joint conduit - conduit > Joint conduit - conduit

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Coupling for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 16 mm - Length 80 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
UV resistant	Yes	**Quality of surface coating**	Uncoated	**Surface polished**	No
Surface brushed	No	**Suitable for nominal tube diameter**	16 mm	**Two-part**	No
With inspection opening and cover	No	**With lock function**	No	**Type of lock function**	Other
Material sealing	Rubber	**With outer thread**	No	**With inner thread**	No
Separable	No	**Eccentric**	No		

Technical Characteristics

length	80 mm

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Raccordi IP65_EM182_2023.pdf

Barcode

8050507871940

Pack

10 NR

0.143 [kg]

8050507871957

Cardboard

350 NR

0.39x0.295x0.3 [m]

5.005 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.