

EC75120

**JOINT PIPE-PIPE IP65 Ø20 mm - GREY
- SPEED SYSTEM**



Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Joint conduit - conduit > Joint conduit - conduit

Technical Symbols/Marks/Approvals

IP65	UL94 V0	GWT 960°	IK07	CE	RoHS II		MADE IN ITALY
------	------------	-------------	------	----	---------	--	---------------------

Norms

EN 61386-1 EN 61386-21

Description

Coupling for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 20 mm - Length 80 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

Material	Plastic	Material quality	Polyvinyl chloride (PVC)	Halogen free	No
Surface protection	Untreated	Colour	Grey	Model	Plug-in
UV resistant	Yes	Quality of surface coating	Uncoated	Surface polished	No
Surface brushed	No	For nominal tube diameter	20 mm	Two-part	No
With inspection opening and cover	No	With lock function	No	Type of lock function	Other
Material sealing	Rubber	With outer thread	No	With inner thread	No
Separable	No	Eccentric	No		

Technical Characteristics

length 80 mm

Documentation available for download



Barcode



8050507871964

Pack

10 NR

0.175 [kg]



8050507871971

Cardboard

200 NR

0.39x0.295x0.21 [m]

3.5 [kg]