

EC75125

**JOINT PIPE-PIPE IP65 Ø25 mm - GREY
- SPEED SYSTEM**



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Joint conduit - conduit > Joint conduit - conduit

Technical Symbols/Marks/Approvals

| | | | | | | | |
|------|------------|-------------|------|----|---------|--|---------------|
| IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | | MADE IN ITALY |
|------|------------|-------------|------|----|---------|--|---------------|

Norms

EN 61386-1 EN 61386-21

Description

Coupling for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 25 mm - Length 80 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000939 - Coupler for installation tubes

| | | | | | |
|------------------------------------------|-----------|-----------------------------------|--------------------------|------------------------------|---------|
| Material | Plastic | Material quality | Polyvinyl chloride (PVC) | Halogen free | No |
| Surface protection | Untreated | Colour | Grey | Model | Plug-in |
| UV resistant | Yes | Quality of surface coating | Uncoated | Surface polished | No |
| Surface brushed | No | For nominal tube diameter | 25 mm | Two-part | No |
| With inspection opening and cover | No | With lock function | No | Type of lock function | Other |
| Material sealing | Rubber | With outer thread | No | With inner thread | No |
| Separable | No | Eccentric | No | | |

Technical Characteristics

length 80 mm

Documentation available for download



Barcode



8050507871995

Pack

10 NR

0.275 [kg]



8057711597130

Cardboard

200 NR

0.39x0.295x0.3 [m]

5.5 [kg]