

EC75232



**JOINT PIPE-SPIRAL CONDUIT IP65
Ø32-25 mm - GREY - SPEED SYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit - spiral conduit > Conduit joints (spiral-rigid) - different diameters



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a spiral conduit of different diameters, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Pipe diameter 32 mm - Conduit diameter 25 mm

Etim

GROUP EG000003 - Protective hose systems
CLASS EC001172 - Coupler for corrugated plastic hoses

Degree of protection (IP)	IP65	Material	Plastic	Material quality	Other
Colour	Grey	Model	Straight	Working temperature	-5-60 °C
Nominal size	25-32 mm				

Barcode



8050507872121

Pack

10 NR

0.34 [kg]



8050507872138

Cardboard

100 NR

0.39x0.295x0.21 [m]

3.4 [kg]