

EC75332



BEND 90° IP65 Ø32 mm - GREY - SPEED SYSTEM



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > 90° bend

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21

Description

90° bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 32 mm - bending radius 110 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

| | | | | | |
|---|-----------|--|----------------------------|--|---------|
| Material | Plastic | Material quality | Polyvinyl chloride (PVC) | Halogen free | No |
| Surface protection | Untreated | Colour | Grey | Model | Plug-in |
| Diameter | 32 mm | Flexible | No | UV resistant | Yes |
| Quality of surface coating | Uncoated | Surface polished | No | Surface brushed | No |
| Compressive strength class according to EN 61386-1 | None | Impact strength class according to EN 61386-1 | Medium (class 3 / 2 Joule) | For nominal tube diameter | 32 mm |
| With sleeve | Yes | Two-part | No | With inspection opening and cover | No |
| Radius | 110 mm | Bend angle | 90 ° | | |

Documentation available for download



Barcode



8050507872244

Pack

10 NR

0.762 [kg]



8050507872251

Cardboard

50 NR

0.39x0.295x0.3 [m]

3.81 [kg]