

**EC75350**

**BEND 90° IP65 Ø50 mm - GREY - SPEED SYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > 90° bend



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-21

**Description**

90° bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 50 mm - bending radius 172 mm

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC000936 - Bend for installation tubes**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Surface protection</b>	Untreated	<b>Colour</b>	Grey	<b>Model</b>	Plug-in
<b>Diameter</b>	50 mm	<b>Flexible</b>	No	<b>UV resistant</b>	Yes
<b>Quality of surface coating</b>	Uncoated	<b>Surface polished</b>	No	<b>Surface brushed</b>	No
<b>Compressive strength class according to EN 61386-1</b>	None	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>For nominal tube diameter</b>	50 mm
<b>With sleeve</b>	Yes	<b>Two-part</b>	No	<b>With inspection opening and cover</b>	No
<b>Radius</b>	172 mm	<b>Bend angle</b>	90 °		

## Documentation available for download



## Barcode



8050507872282

### Cardboard

12 NR

0.39x0.295x0.21 [m]

3 [kg]