elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



EC75425

JOINT PIPE-SPIRAL CONDUIT IP65 Ø25-25 mm - GREY - SPEED SYSTEM

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit - spiral conduit > Conduit joints (spiral-rigid) - same diameters

Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

Connector for the connection between a pipe and a spiral conduit of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Pipe diameter 25 mm - Conduit diameter 25 mm

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001172 - Coupler for corrugated plastic hoses

Degree of protection (IP)	IP65	**Material**	Plastic	**Material quality**	Other
Colour	Grey	**Model**	Straight	**Working temperature**	-5-60 °C
Nominal size	25-25 mm				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050507872336

Pack

10 NR

0.5 [kg]

8050507872343

Cardboard

160 NR

0.39x0.295x0.21 [m]

8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.