

## EC75432

### JOINT PIPE-SPIRAL CONDUIT IP65 Ø32-32 mm - GREY - SPEED SYSTEM



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler conduit - spiral conduit > Conduit joints (spiral-rigid) - same diameters

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-21

### Description

Connector for the connection between a pipe and a spiral conduit of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Pipe diameter 32 mm - Conduit diameter 32 mm

### Etim

**GROUP EG000003 - Protective hose systems**

**CLASS EC001172 - Coupler for corrugated plastic hoses**

<b>Degree of protection (IP)</b>	IP65	<b>Material</b>	Plastic	<b>Material quality</b>	Other
<b>Colour</b>	Grey	<b>Model</b>	Straight	<b>Working temperature</b>	-5-60 °C
<b>Nominal size</b>	32-32 mm				

## Barcode



8050507872350

**Pack**

10 NR

0.668 [kg]



8050507872367

**Cardboard**

80 NR

0.39x0.295x0.21 [m]

5.344 [kg]