elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

# EC75620

## FLEXIBLE BEND PIPE-PIPE IP65 Ø20 mm - GREY - SPEED SYSTEM

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > Flexible bend (conduits-conduits)

### Technical Symbols/Marks/Approvals

IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY

### Norms

EN 61386-1 EN 61386-21

## Description

Flexible bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. Soft internal sealing ring for pipe tolerance compensation. IP65 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 20 mm - length 230 mm

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

### CLASS EC000936 - Bend for installation tubes

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Polyvinyl chloride (PVC) | **Halogen free** | No |
| **Surface protection** | Untreated | **Colour** | Grey | **Model** | Plug-in |
| **Diameter** | 20 mm | **Flexible** | Yes | **UV resistant** | Yes |
| **Quality of surface coating** | Uncoated | **Surface polished** | No | **Surface brushed** | No |
| **Compressive strength class according to EN 61386-1** | None | **Impact strength class according to EN 61386-1** | Medium (class 3 / 2 Joule) | **Suitable for nominal tube diameter** | 20 mm |
| **With sleeve** | Yes | **Two-part** | No | **With inspection opening and cover** | No |
| **Radius** | 200 mm | **Bend angle** | 90 ° | | |

## Technical Characteristics

| | |
|---|---|
| **length** | 230 mm |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode

8050507872558

**Pack**

50 NR

2.375 [kg]

8050507872565

**Cardboard**

200 NR

0.605x0.4x0.26 [m]

9.5 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.